

ThinkCentre M75n Platform Specifications

Product Specifications Reference (PSREF)

Processor	AMD Ryzen 3 / 5 PRO series processor						Manageability Security chip Security features	Dash 1.1/1.2 Discrete TPM 2.0, TCG Certified <ul style="list-style-type: none"> Security slot (in rear for optional Kensington® MicroSaver® cable) Chassis intrusion switch Power-on password Administrator password Hard disk password <ul style="list-style-type: none"> Boot sequence control Boot without keyboard and mouse Individual USB port disablement Smart USB protection, allows keyboard/mouse only, blocks all storage devices 						
	Processor	Cores / Threads	Frequency Base/Max	L2 / L3 Cache	Memory Support (Up to)	Integrated Graphics								
	Ryzen 3 PRO 3300U	4 / 4	2.1 / 3.5 GHz	2 MB / 4MB	DDR4-2400	Radeon Vega 6								
Ryzen 5 PRO 3500U	4 / 8	2.1 / 3.7 GHz	2 MB / 4MB	DDR4-2400	Radeon Vega 8									
Memory	8GB / DDR4-2400* / soldered to systemboard, no sockets, dual-channel capable, non-ECC * System automatically clocks down for the processors with lower memory controller						Keyboard	<i>Some:</i> Lenovo Calliope Keyboard (USB connector), black <i>Some:</i> Lenovo Traditional Keyboard (USB connector), black <i>Some:</i> Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black						
Storage	Support up to two M.2 SSD (one PCIe x4, one PCIe x2) <i>Some:</i> M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4* <i>Some:</i> M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 2 * M.2 SSD in PCIe 3.0 x2 M.2 slot can only run at PCIe 3.0 x2						Mouse	<i>Some:</i> Lenovo Calliope Mouse (USB connector), black <i>Some:</i> Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black <i>Some:</i> Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black						
RAID	None						Mechanical	Nano (0.35L), black color; metal case Three M.2 slots: two for M.2 SSD (one PCIe 3.0 x4 and one PCIe 3.0 x2) and one for WLAN						
Optical	None													
Graphics	AMD Radeon™ Vega 6/8 Graphics in processor, uses main memory, DirectX® 12, one DisplayPort™, one USB 3.2 Type-C Gen2 with display function, up to 2 independent displays; <i>Max resolution:</i> 3840x2160 (DP)@60Hz; 3840x2160 (Type-C)@60Hz Optional DP to VGA dongle, DP to HDMI dongle, Type-C to VGA dongle, Type-C to HDMI dongle, Type-C to DP dongle						<table border="1"> <thead> <tr> <th></th> <th>Dimensions (WxDxH)</th> <th>Weight (Approx.)</th> </tr> </thead> <tbody> <tr> <td>M75n (with fan, 0.35L)</td> <td>7.05" X 3.46" X 0.87" 179mm X 88mm X 22mm</td> <td>1.11 lb (0.505 kg), vary by config</td> </tr> </tbody> </table>			Dimensions (WxDxH)	Weight (Approx.)	M75n (with fan, 0.35L)	7.05" X 3.46" X 0.87" 179mm X 88mm X 22mm	1.11 lb (0.505 kg), vary by config
	Dimensions (WxDxH)	Weight (Approx.)												
M75n (with fan, 0.35L)	7.05" X 3.46" X 0.87" 179mm X 88mm X 22mm	1.11 lb (0.505 kg), vary by config												
Monitor cable	AMD SoC (System on Chip) platform Optional DP to VGA dongle, DP to HDMI dongle, Type-C to VGA dongle, Type-C to HDMI dongle, Type-C to DP dongle						Mounting	<i>Some:</i> VESA mount bracket kit, supports VESA 75mm <i>Some:</i> VESA mount bracket kit with adapter holder, supports VESA 75mm <i>Some:</i> DIN rail mount bracket kit						
Chipset							Floor Stand	None						
Front ports (Std.)*	1x USB 2.0, 1x USB 3.2 Gen 2, 1x USB 3.2 Type-C Gen 2, one headphone / microphone combo jack (3.5mm)						Power supply	65 watts adapter, autosensing, 89% PSU (Not for TIO models)						
Rear ports (Std.)*	1x USB 2.0, 1x USB 3.2 Gen2, 1x USB 3.2 Type-C Gen 2 (with display function, support power-in [20V and >45W]), 1x ethernet (RJ-45), 1x DisplayPort * Depending on many factors, actual data transfer speed may be lower than theoretical speed						Limited warranty	<i>Some:</i> 1-year, limited onsite service / service upgrades available <i>Some:</i> 3-year, limited onsite service / service upgrades available						
Audio support	Realtek ALC233 / internal speaker (1watt)						Preload	Preloaded operating system <i>Some:</i> Windows® 10 Pro 64-bit <i>Some:</i> Windows 10 Home 64-bit <i>Some:</i> Windows 10 IoT Enterprise (only available via special bid model)						
WLAN	<i>Some:</i> 11ac wireless, M.2 Card, Realtek RTL8822CE (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 <i>Some:</i> 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 <i>Some:</i> 11ac wireless, M.2 Card, Intel Wireless-AC 9260 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2						Environment	ENERGY STAR® 8.0, EPEAT™ Silver rating, ErP Lot 3, TCO 8.0 (coming soon), TUV ultra low noise verified (on some models), RoHS, WEEE, REACH						
Bluetooth	<i>Some:</i> Bluetooth 4.2 / 5.0 wireless, integrated in Wi-Fi + BT combo adapter						MIL-SPEC test	MIL-STD-810H (coming soon)						
Ethernet	Gigabit ethernet, Realtek RTL8111FP-CG, Wake on LAN®						Accessories	For compatible accessories, please go to http://smartfind.lenovo.com						

Note: The specifications above may not be available in all regions.

Lenovo, May 2020